

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 900 705 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
10.03.1999 Bulletin 1999/10

(51) Int. Cl.⁶: B60R 21/32

(21) Application number: 98202639.5

(22) Date of filing: 05.08.1998

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: 03.09.1997 US 923020

(71) Applicant:

DELCO ELECTRONICS CORPORATION
Kokomo Indiana 46902 (US)

(72) Inventors:

- Murphy, Morgan Daniel
Kokomo, Indiana 46901 (US)

• Myers, Robert Joseph

Russiaville, Indiana 46979 (US)

• Roe, Pamela Ann

Kokomo, Indiana 46901 (US)

• Piper, William Lloyd

Kokomo, Indiana 46901 (US)

(74) Representative:

Denton, Michael John et al

Delphi Automotive Systems

Centre Technique Paris

117 avenue des Nations

B.P. 60059

95972 Roissy Charles de Gaulle Cedex (FR)

(54) Vehicle occupant weight estimation apparatus

(57) An improved weight estimation apparatus includes a closed elastomeric bladder filled with fluid and installed in the foam cushion of a vehicle seat bottom, with at least one pressure sensor installed in a closed exit port of the bladder. A temperature sensor disposed in proximity to the bladder provides a temperature signal, and a controller estimates the weight of the occupant based on the temperature and pressure signals. The pressure sensor is preferably configured to sense the gage pressure -- that is, the differential pressure between the fluid and atmospheric pressure -- at the center of gravity of the fluid in order to provide a stable output independent of changing atmospheric pressure and changing orientation of the bladder due to vehicle pitch and roll.

EP 0 900 705 A2

Description

Technical Field

[0001] This present invention relates to an apparatus 5 for estimating the weight of a vehicle occupant.

Background of the Invention

[0002] Vehicle occupant detection systems are useful 10 in connection with air bags and other pyrotechnically deployed restraints as a means of judging whether, and how forcefully, to deploy the restraint. One fundamental parameter in this regard is the weight of the occupant, as weight may be used as a criteria to distinguish 15 between an adult and an infant or small child.

[0003] One prior weight estimation technique is to install an array of variable resistance pressure sensitive elements in the seat, and to sum the individual pressures to determine occupant weight. A restraint system 20 based on this technique is shown and described in the U.S. Patent No. 5,474,327, issued on December 12, 1995, and assigned to the assignee of the present invention. In practice, however, such systems tend to be relatively costly to implement, and require a significant 25 amount of signal processing for proper calibration and weight estimation.

[0004] Another possible technique is to instrument the seat frame with strain detectors, for example. However, 30 this technique is also costly to implement, and cannot be readily applied to existing seat structures not designed for strain sensing.

[0005] Accordingly, a simple weight estimation apparatus is desired. Ideally, the apparatus would be easy to 35 install in existing seat designs, and would require a minimum amount of processing to arrive at a weight estimation sufficiently accurate to enable occupant-appropriate restraint deployment decisions.

Summary of the Invention

[0006] The present invention is directed to an improved weight estimation apparatus satisfying the desired characteristics described above. Fundamentally, the apparatus comprises a closed, elastomeric 45 bladder filled with fluid and installed in the foam cushion of a vehicle seat bottom, with at least one pressure sensor installed in a closed exit port of the bladder. A temperature sensor disposed in proximity to the bladder provides a temperature signal, and a controller estimates the weight of the occupant based on the temperature and pressure signals. An additional bladder and sensor may be installed in the foam cushion of the vehicle seat back, if desired.

[0007] In a preferred embodiment, the pressure sensor is configured to sense the gage pressure -- that is, the differential pressure between the fluid and atmospheric pressure -- at the center of gravity of the fluid in 55

order to provide a stable output independent of changing atmospheric pressure and changing orientation of the bladder due to vehicle pitch and roll. Alternatively, the sensor may be configured to detect absolute pressure, and a second absolute pressure sensor responsive to atmospheric pressure may be used to compensate for changes in atmospheric pressure, and multiple sensors may be used to detect and compensate for the changing orientation.

[0008] A vehicle occupant weight estimation apparatus in accordance with the present invention is characterized by the features specified in Claim 1.

Brief Description of the Drawings

[0009] The present invention will now be described, by way of example, with reference to the accompanying drawings, in which:-

Figure 1 is a system diagram illustrating a passenger seat of a vehicle equipped with fluid-filled bladders and a controller for estimating the weight of a seat occupant in accordance with this invention;

Figure 2 is a cross-section view of a foam seat cushion and fluid-filled bladder according to this invention;

Figures 3A-3C depict a bladder and pressure sensor configuration according to a preferred embodiment of this invention;

Figure 4 is a block diagram of the controller of Figure 1, in the context of an air bag deployment system;

Figure 5 is a graph depicting pressure sensor output voltage as a function of occupant weight, as used in the system of Figure 4; and

Figure 6 is a flow chart representative of computer program instructions executed by the controller of Figure 4.

Description of the Preferred Embodiment

[0010] Referring to the drawings, and particularly to Figure 1, the reference numeral 10 generally designates a vehicle occupant weight estimation apparatus according to this invention. The vehicle seat 12 is supported on a frame 14, and includes foam cushions 16 and 18 on the seat bottom and back. A vacuum formed polymeric bladder 20 disposed in the foam cushion 16 substantially parallel with the central seating surface contains a fluid such as silicone which is non-corrosive, and not subject to freezing at extreme ambient temperatures.

[0011] Referring to Figures 1 and 2, the bladder 20 includes a fill tube or exit port 22 which is sealed about the inlet port 24 of a pressure sensor 26, which provides an electrical output signal on line 28 indicative of the fluid pressure in the bladder 20. A temperature sensor 30 located in proximity to the bladder 20 provides an electrical output signal on line 32 indicative of the blad-

der and foam temperature. The sensor 30 can be provided as a separate sensor as indicated in Figure 1, or may be integrated with the pressure sensor 26.

[0012] The electrical pressure and temperature signals on lines 28 and 32 are provided as inputs to a controller 50, which determines if the seat 12 is occupied and estimates the weight of the occupant based on the pressure and temperature signals, possibly in combination with other inputs, such as an atmospheric pressure signal provided pressure sensor 52. An electrical output signal indicative of the weight estimation is provided on line 54, and may be used, for example, as a factor in determining whether and how forcefully to deploy air bags or other pyrotechnically deployed restraints in a crash event.

[0013] The controller 50 may be mechanized with a suitably programmed microprocessor, as described below in reference to Figures 4-6. The fluid has a nominal or unloaded pressure which provides a baseline measurement, and the pressure increases monotonically with occupant weight applied to the cushion 16. The temperature measurement is used to compensate the weight measurement for corresponding changes in foam and bladder stiffness, to provide a weight measurement that is insensitive to temperature variations.

[0014] Preferably, the pressure sensor 26 is configured to sense the differential or gage pressure of the fluid - that is, the pressure difference between atmospheric pressure and bladder fluid pressure - in order to provide a pressure measurement that is insensitive to atmospheric pressure variations due to changing weather patterns or altitude. In this case, the sensor 26 includes a second inlet (not shown) open to atmospheric pressure.

[0015] Alternately, the sensor 26 may provide an absolute pressure measurement of the bladder fluid, and the controller 50 may compensate the measurement for atmospheric pressure variations by reducing the fluid pressure measurement by the atmospheric pressure measurement provided by sensor 52.

[0016] As indicated in Figure 1, a second bladder 34, pressure sensor 36 and temperature sensor 38 may be provided in the foam seat back cushion 18 to provide information regarding the weight or force exerted against the seat back 18 by the occupant. In many vehicles, however, it has been found that a seat bottom bladder alone provides sufficient information to accurately estimate occupant weight.

[0017] In mechanizing the present invention, it was discovered that, depending on the placement of the exit port 22, the pressure sensed by sensor 26 experiences significant variability with changes in the orientation of the bladder. Specifically, the sensed pressure changes whenever the center of gravity of the bladder fluid changes relative to the location of the exit port 22. This can occur when there is fore-aft pitch due to uphill or downhill operation of the vehicle, or when there is roll.

[0018] One solution to the above-described problem

is to use multiple pressure sensors located in the front, rear and side of the bladder 20. In this case, the pressures sensed by the front and rear pressure sensors are averaged to compensate for pitch, and the pressure sensed by the side sensor is used to compensate for roll. The exit ports in the case of multiple sensors should be equal in diameter and length to avoid imbalance in the various pressure drops.

[0019] A preferred approach to compensating for pitch and roll is to determine the location of the center of gravity of the fluid in a given application, and to sense the fluid pressure at the center of gravity. This can be done, as shown in Figures 3A-3C, by means of a tube 66 coupled to the sensor 26, with the bladder 20 sealed around the tube 66 at a shoulder 67 thereof. The tube 66, depicted in detail in Figures 3B-3C, is configured with side ports 68, 70 to ensure open fluid communication between the bladder fluid and the sensor 26 at all times. Preferably, the length of tube 66 is minimized by placing the pressure sensor inlet 24 in close proximity to bladder 20, as shown in Figures 3A and 3C. However, the sensor 26 may be located remote from the bladder if required by simply extending the tube 66; in this case, the tube 66 should have a relatively large diameter to minimize the resulting pressure drop.

[0020] As also seen in Figure 3A, the bladder 20 generally conforms to the shape of the seat bottom 16. Various openings and crimp areas 70 allow the bladder 20 to conform to the shape of the seat cushion, while other crimp areas 72 are required to properly position the bladder in the vacuum form equipment. The crimp areas 70, 72 do not degrade the pressure measurement since the fluid can freely flow in and out of the various areas or cells of the bladder 20. In fact, the crimp areas can be advantageously used to reduce the overall volume, and thus the weight, of the bladder 20, provided that friction losses from fluid flow within the bladder 20 are minimized.

[0021] Figure 4 depicts the occupant weight estimation apparatus of the present invention in the context of an air bag deployment system in which the controller 50 provides an output signal on line 54 indicating whether deployment should be inhibited or allowed based on sensed occupant weight. Vehicle ignition voltage Vign, which may be + 12 VDC, is supplied to controller 50 via line 80, and an internal voltage regulator 82 provides a regulated system voltage of + 5 VDC on lines 84 and 86. The system and ground voltages are supplied to source voltage terminals of the pressure sensor 26, the temperature sensor 30 (which may be a thermistor), and a microprocessor 88. The microprocessor 88 has four analog-to-digital input channels A/D 1-A/D 4 which receive the ignition voltage Vign, the system voltage of voltage regulator 82, the temperature sensor output voltage on line 32, and the pressure sensor output voltage on line 28.

[0022] Based on the above-described inputs, the microprocessor determines the occupant weight, and

based on predetermined criterion, whether air bag deployment should be inhibited or allowed. In the illustrated control strategy, air bag deployment is to be inhibited for occupants below a predetermined weight, referred to herein as the threshold weight.

[0023] In general, once the occupant weight estimation system 10 is installed in a vehicle, the relationship between occupant weight and sensed pressure (compensated for system voltage variations) is empirically determined at a variety of temperatures. In a system as suggested in Figure 1, the data can be used to construct either a mathematical model or a multidimensional look-up table of occupant weight as a function of temperature and pressure sensor output voltage, with the model or table programmed into the microprocessor and used to determine and output the occupant weight on line 54. In the system of Figure 4, however, the output merely indicates whether the occupant is above or below the threshold weight, within the system tolerance constraints. In this case, the empirically determined data may be plotted as shown in Figure 5, and used to develop a pressure sensor threshold voltage for determining whether deployment should be inhibited or allowed. For the data represented in Figure 5, for example, the lines designated as upper limit UL and lower limit LL bound the pressure sensor output voltage variability for any given occupant weight. Given a threshold weight, such as 47.7 kg (105 lb.) for example, the lower limit LL defines a threshold voltage which is the minimum voltage, approximately 1.82 volts, one would expect to see for an occupant weighing 47.7 kg (105 lb.).

[0024] A simple control algorithm based on the above described threshold voltage is depicted in the flow diagram of Figure 6, where the block 90 designates a series of program instructions executed at the initiation of vehicle operation for initializing the various registers and variable values. In this case, the system output variable, STATUS, is initially set to a state which inhibits deployment. Thereafter, the block 92 is executed to repeatedly sample the pressure sensor output voltage for a predefined interval to obtain an average output voltage AVGOUT, and to compensate AVGOUT for the temperature sensed by temperature sensor 30. If the temperature compensated value of AVGOUT is less than the threshold voltage of 1.82 volts, as determined at block 94, the block 96 is executed to set STATUS to a state which inhibits deployment. If the temperature compensated value of AVGOUT is greater than a hysteresis threshold voltage corresponding to, say 48.6 kg (107 lb.), as determined at block 98, the block 100 is executed to set STATUS to a state which allows deployment. If AVGOUT is between the two threshold voltages, the state of STATUS is maintained unchanged, as indicated by the blocks 102-106.

[0025] It should be understood that the simple control described above is exemplary in nature, and could be modified to include adaptive updating of the thresholds, or to provide a more precise output as described above

in reference to Figure 1, for example.

Claims

1. Apparatus for estimating the weight of an occupant of a seat (12) in a motor vehicle, the seat (12) having a foam cushion bottom (16), the apparatus comprising:
 - a closed elastomeric bladder (20) disposed in the foam cushion bottom (16), the bladder (20) being substantially filled with fluid, and having a exit port (22);
 - a pressure sensor (26) coupled to said exit port (22) for sealing said exit port (22) and for sensing the pressure of said fluid; a temperature sensor (30) for sensing a temperature in proximity to said bladder (20); and
 - control means (50) for estimating the weight of the occupant based on the sensed fluid pressure and the sensed temperature.
2. The apparatus of Claim 1, where the pressure sensor (26) is configured to sense a differential pressure between the pressure of the fluid and atmospheric pressure.
3. The apparatus of Claim 1, wherein the pressure sensor (26) is configured to sense an absolute pressure of the fluid, and the control means (50) includes an absolute pressure sensor (52) for detecting the atmospheric pressure, the occupant weight being estimated based on a difference between the sensed fluid pressure and the sensed atmospheric pressure.
4. The apparatus of Claim 1, where the pressure sensor (26) is configured to sense the pressure of the fluid at a center of gravity of the fluid.
5. The apparatus of Claim 4, including a tube (66) having an inlet positioned at the center of gravity of the fluid and an outlet coupled to said pressure sensor (26), the bladder (20) being sealed around said tube (66) between said inlet and said outlet.
6. The apparatus of Claim 1, where the temperature sensor (30) is integrated with the pressure sensor (26).
7. The apparatus of Claim 1, wherein said control means (50) provides an input (54) to an air bag deployment system, said input indicating whether deployment should be inhibited or allowed based on the estimated weight of the occupant.
8. The apparatus of Claim 1, wherein said control means (50) provides a status signal to an air bag

deployment system, and includes means (88) for
sampling an output of said pressure sensor (26),
compensating said sampled output for temperature
based on an output of said temperature sensor
(30), and comparing said compensated pressure
sensor output to a threshold signal corresponding
to a threshold occupant weight; and means (88) for
setting said status signal to a value for inhibiting air
bag deployment when said comparison indicates
that the estimated occupant weight is less than said
threshold weight, and for setting said status signal
to a value for allowing air bag deployment when
said comparison indicates that the estimated occu-
pant weight is greater than said threshold weight.

15

20

25

30

35

40

45

50

55

Fig.1.




Fig.2.




Fig.3a.




Fig.3b.




Fig.3c.




Fig.4.




Fig.5.





Fig.6.



(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 900 705 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
02.02.2000 Bulletin 2000/05

(51) Int. Cl.⁷: **B60R 21/32**, B60R 21/00,
B60N 2/00

(43) Date of publication A2:
10.03.1999 Bulletin 1999/10

(21) Application number: 98202639.5

(22) Date of filing: 05.08.1998

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

- Myers, Robert Joseph
Russiaville, Indiana 46979 (US).
- Roe, Pamela Ann
Kokomo, Indiana 46901 (US)
- Piper, William Lloyd
Kokomo, Indiana 46901 (US)

(30) Priority: 03.09.1997 US 923020

(71) Applicant:
DELCO ELECTRONICS CORPORATION
Kokomo Indiana 46902 (US)


(74) Representative:
Denton, Michael John et al
Delphi Automotive Systems
Centre Technique Paris
117 avenue des Nations
B.P. 60059
95972 Roissy Charles de Gaulle Cedex (FR)

(72) Inventors:
• Murphy, Morgan Daniel
Kokomo, Indiana 46901 (US)

(54) Vehicle occupant weight estimation apparatus

(57) An improved weight estimation apparatus includes a closed elastomeric bladder filled with fluid and installed in the foam cushion of a vehicle seat bottom, with at least one pressure sensor installed in a closed exit port of the bladder. A temperature sensor disposed in proximity to the bladder provides a temperature signal, and a controller estimates the weight of the occupant based on the temperature and pressure signals. The pressure sensor is preferably configured to sense the gage pressure -- that is, the differential pressure between the fluid and atmospheric pressure -- at the center of gravity of the fluid in order to provide a stable output independent of changing atmospheric pressure and changing orientation of the bladder due to vehicle pitch and roll.

Fig.1.



EP 0 900 705 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 20 2639

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	US 5 176 424 A (TOBITA KOJI ET AL) 5 January 1993 (1993-01-05)	1,2	B60R21/32 B60R21/00 B60N2/00
Y	* abstract * * column 6, line 56 - line 63; figure 2 * * column 7, line 57 - line 65; figure 4 *	7,8	
Y,P	WO 98 26961 A (AUTOMOTIVE SYSTEMS LAB) 25 June 1998 (1998-06-25) * abstract; figures 1-8 *	7,8	
A,P	WO 98 30411 A (AUTOMOTIVE SYSTEMS LAB) 16 July 1998 (1998-07-16) * abstract; figures 1-10 *	1-8	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			B60N B60R
Place of search		Date of completion of the search	Examiner
THE HAGUE		13 December 1999	Gaillard, A
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03 82 (P04C01)

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 98 20 2639

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

13-12-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5176424 A	05-01-1993	JP 2077211 A	16-03-1990
		JP 2041115 A	09-02-1990
		EP 0345806 A	13-12-1990
WO 9826961 A	25-06-1998	US 5957491 A	28-09-1999
		EP 0885139 A	23-12-1999
WO 9830411 A	16-07-1998	CA 2248207 A	16-07-1998
		EP 0892728 A	27-01-1999

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.